



# SilverHawk Type II Chevy G-30 Van



## CHASSIS

- Chevy G-30 Van, 155" WB, 9,600 GVWR
- Front Axle- 4600 GAWR, Rear Axle- 6084 GAWR
- DuraMax 6.6L DIT V-8 Diesel w/5 Spd Trans
- Optional Vortec 6.0L Gas w/6 Spd Trans
- Diesel Rear Axle- 3.73:1 gear ratio
- Gas Rear Axle- 3.42:1 gear ratio
- Alternators- Dual 145 amp
- 37-gallon fuel capacity
- LT245/75R16.0 "E" black sidewall tires
- Spare tire- matching, mounted under rear body
- Sliding curbside door- 60/40 swing-out
- Power door locks- Power windows
- OEM side mirrors w/convex, turn signals
- Tilt steering wheel; Cruise Control
- AM/FM/CD/Clock radio with 4-speakers
- Dual Captain's chairs with tilt back
- Black rubber formed floor mats
- Back-Up Alarm- 97 decibel
- YF2 Ambulance Builder's Prep Package
- DEF Tank, 5.83 gal, fill with fuel fill on street side body (Not Available on Gas Engine)

## CHASSIS EXTERIOR

- Roof- Steel roll cage w/raised fiberglass roof cap
- MEDIX ADP rear bumper w/flip-up center step
- MEDIX ADP fixed front and rear mud flaps

## ENVIRONMENTAL SYSTEMS

- Combination 36K BTU heat, 32K BTU A/C free blow system
- 720 CFM multi-speed fan
- Exhaust fan- 2-speed, 520 CFM

## POWER DISTRIBUTION & CONTROL

- OEM dual battery system- 1540 CCA total
- Digital volt/amp meter
- Basic, easy maintenance relay/circuit breaker system- Front and rear switch panels w/internal LED backlighting; switch for each critical function and spare locations for options

- Wiring- GXL, point-to-point, color-coded, stamped labels; wiring sized to voltage requirements of each circuit
- Front Console, floor-mounted formed ABS body w/cup holders
- Rear control panel mounted in Action Area
- Shoreline- 125V-20 amp, 60 Hz covered receptacle
- Battery charger- Standard 45Amp
- Inverter- prewire
- 125V outlets- (2)
- 12VDC outlets- (2)
- Radio Power/Ground- (2) with antenna coax

## EMERGENCY LIGHTING & SIREN

- Light Bar, front- Code 3 "Excalibur" Halogen (2) red, (1) clear
- Exterior Body- 9x7 Red Halogen on corners each side, front and rear, 9x7 Amber Halogen (1) rear center, 9x7 Clear Halogen front center
- Grille- (2) 7x3 Red LED w/chrome bezels
- Intersection- (2) 7x3 Red Halogen w/chrome flanges
- Scene Lights- (4) 9x7 Halogen 8°-32° Halogen
- Load Lights- (2) 9x7 Halogen 8°-32° Halogen
- Hand-held Spotlight- 400,000 CP, in cab
- Siren- 200 watt w/NC microphone in front console
- Siren Speakers- (2) 100 watt thru front bumper

## PATIENT COMPARTMENT INTERIOR

- Formed fiberglass ceiling panel
- Laminated wood cabinetry- Full SS cabinet wall w/overhead, Stair Chair pocket, walk-thru cabinets w/locking drug cabinet
- Acrylic sliding doors w/extruded pull handles
- Patient Compartment- Interior Headroom- 66"
- Cabinet to Squad Bench Aisle- 37"
- Cab to Patient Compartment walk-thru
- Patient Compartment Insulation- 2.5" fiberglass

- Squad Bench- (3) belted seating positions; rear access to Backboard Storage- holds 16" or 18" boards; hinged lid for interior access
- ALS Cabinet- multi-level shelves
- Technician's Seat- rear facing steel storage base w/ cushion and backrest and Type I lap belt
- Interior Lighting- (6) Halogen dome lights recessed in ceiling w/5-minute check-out timer; LED strip light in Action Area.
- Grab handles on each door interior
- Overhead grab rail in ceiling
- Heavy Duty seamless vinyl cushions w/3" foam

## PATIENT CARE SYSTEMS

- Suction Aspirator- disposable container and hose hard plumbed to 12VDC vacuum pump.
- Oxygen outlets- (2) in Action Area, (1) over Squad Bench
- Oxygen Cylinder Storage- Located in vertical cabinet w/recessed floor well at rear of squad bench; steel bracket w/ratchet straps and top collar
- IV Holders- (2) chrome clip-style hangers in ceiling
- Cot Mount- FW # 175-2, single position, removable

## PAINT, DECAL, LETTERING, SIGNAGE

- SOL Decals- standard
- Paint Stripe- optional
- Lettering- optional
- (2) NO SMOKING, (2), FASTEN SEATBELTS

## WARRANTIES

### CONVERSION:

- Electrical- 72 months/72,000 miles
- Limited- 12 months/12,000 miles
- Paint- if applicable- 48 months