

DEALER: XYZ Dealer
CUSTOMER: XYZ Emergency Ambulance
 Street or P.O. Box _____
 City, State, Zip _____
 Customer Contact: _____
 Sales Associate: _____
VIN#: To be assigned by MEDIX

Chassis Model Yr		2017
MEDIX Model		MSV-II 157 Type I
CHASSIS		Ford F-450 XLT 4x4, 6.7L DIT Diesel, 169" WB, 16,500 GVWR
BODY		157"L x 96" W x 72" Interior Headroom
QTY	STD/OPT	Description
1	16-1000-FD	Chassis & Conversion
	6-8 week lead time	Liquid Spring Suspension Installation by Utility Bodywerks DS129FS3, see quote, the kit will be ordered through Utility Bodywerks; Requires Dump cancel switch that Medix will order and install - installed at the Curbside rear door on the wall - "Air Dump Override" - p/n: MX09166.
01-		Flooring & Interior Colors
1	STD	Cabinets: Laminated Wood- (Specify Color) Color:
1	STD	Upholstery: (Specify Color) Color: Brand: EVS
1	STD	Flooring: Lonseal- LonPlate (Diamond Plate) (Specify Color) Color:
02-		Body & Chassis
1	STD	This chassis is equipped with a Diesel Exhaust Fluid (DEF) System to meet the EPA Diesel Emissions Standards.
1	STD	All Exterior compartments coated with a light gray rubberized urethan material.
1	STD	Pass-Thru - No sliding Lexan, just OEM P/T
1	STD	Compartment Lights: Optronics ILL36CB LED Compartment lights- ALL Models Locate: (1) Ceiling of Compt #1; (2) in Compt #2- (1) URH, (1) LLH; (1) in ceiling of Compartment #3; (2) in Compt #4/5; (1) in Compt #6.
1	STD	Compartment #1 SS Forward: Smooth Aluminum body, O2 Universal "M" or "H" cylinder storage for STEEL tank, Door w/gas strut hold-open, Sealed access to paddle handle in door panel. Stainless steel sill protector.
1	STD	Compartment #2 SS Center: Smooth Aluminum body, Open Storage, Single access door w/gas strut hold-open. (1) Adjustable aluminum shelf w/DA finish. Sealed access to paddle handles in door panel. Stainless steel sill protector.
1	STD	Compartment #3 SS Rear: 3/4 height, Smooth Aluminum body, Inside/Outside access w/offset for interior monitor shelf aft of CPR seat, (1)- adjustable shelf w/DA finish. Door w/gas strut hold-open. Sealed access to paddle handle in door panel. Stainless steel sill protector.

2	STD	Rear Entry Doors: Dual door system w/exterior/interior, locking paddle handles; fixed glass windows and Cast Grabber hold-opens. Sealed access to paddle handles in door panels. Stainless steel sill protector. Two-piece interior door panel.
1	STD	Compartment #4/5 CS Forward: NO body above floor, ADP interior door panel, ALS Cabinet w/ Inside/Outside access, Full-height, single Door w/gas strut hold-open. Bottom section smooth aluminum body for open storage or optional roll-out battery tray w/removable, latching door.
1	STD	Drop Skirt - 4" on Curbside forward of the rear wheelwell. Requires rub rail to be offset on curbside; fenderette will sit on top of rub rail forward of rear wheel only on curbside; taller front stone guard on passenger side and taller kickplate on passenger side.
1	STD	Curbside Entry Door: Taller for 4" drop skirt. Door handle to remain aligned with Comp #4/5 handle; Single door system w/exterior/interior, locking paddle handles; window w/fixed glass; Gas strut hold-open. Sealed access to paddle handles in door panel. LED Step well light. Stainless steel sill protector. Two-piece interior door panel.
1	STD	Compartment #6 CS Rear: Smooth Aluminum body, Vertical backboard storage w/(2) seat belts restraints; (1) in upper Backboard section, (1) lower across Backboard and Stair Chair Section. Door w/gas strut hold-open. Sealed access to paddle handles in door panel, Stainless steel sill protector. <u>Compartment to be 14.5" Wide and divider located to accommodate 8" wide tracked Stair Chair.</u>
1	STD	Divider: Aluminum w/DA finish, vertical in back Board Compartment #6
1	STD	All Entry Door paddle handle and rotary latching components will include emergency door releases located top and bottom of each door and shall meet the FMVSS 206 30G Test Requirement
1	STD	Power Door Locks: Key Pad, programmable for power door locks NOTE: Ford ONLY (Required for 2017 Type 1)
1	STD	Pass-Thru: With accordion boot.
1	STD	Running Boards: Aluminum diamond plate w/splash guards and Starburst grip punch pattern
1	STD	Fender Flares: Rolled Stainless Steel.
1	STD	Rear Bumper: ADP corner pods w/Dock bumper pads, Center grip-strut flip-up step, powder coated steel frame
2	STD	IV Hangers: (2) Cast black rubber fold-down over knee area of Cot and Squad Bench
3	STD	Mirrors, OEM: (1) heated/remote control on each cab door, (1) on interior windshield
4	STD	Wheel Covers: Stainless steel covers w/Valve Extenders
4	STD	Stone Guards: (3) Std Lower body corners, ADP; (1) 4" taller ADP on Curbside front
1	STD	Kick Plate, Rear: ADP, below rear doors across to corner posts
1	STD	Rub Rails: C-Channel, tapered ends, Lower Body off-set mount with neoprene spacers.
2	STD	Fuel Fill Bezel: Cast aluminum; DEF Fill Bezel: Cast Aluminum
2	STD	Fuel Fill Scuff Plate: Stainless steel, below fuel fill bezel for Type I and DEF Fill bezel.
1	STD	Undercoating: Per Ford QVM Guidelines
03- Brake, Turn & Back-Up Lights		

1	STD	Lights: DOT, Brake/Tail, Turn, Back Up: Whelen 600 Series LED. (Package PNs: 60BTTC, 60A00TAR, 60C00VCR) ILOS
1	STD	DOT Marker Lights: Optronics LED, rubber grommet bezels; (7) MCL11CAB Amber- (5) on front of body as Marker lights, (2) side facing on rear extrusions as Turn Signals; (7) MCL11CRB Red- (5) on rear of Body as Marker lights, (2) side facing as Turn Signals.
	04-	Electrical, Power Distribution, Control Center & Interior Lighting
1	STD	Battery Switch, Automatic: TST CDR-357. Located in Electrical Cabinet.
0	99-0766A	Battery: Additional, (1) OEM, 750 C.C.A. w/single roll-out tray on Type I, IATS batteries under the hood. Battery to be located below ALS in sealed storage area.
1	STD	Front Console/ Switch Panel: Formed Aluminum body powder coated black and attached to chassis floor. Switch panel: Engraved black plastic with LED lighted switches for Emergency Master, Primary/Secondary Modes, Siren/Horn, Left, Rear and Right Floods, Back-Up Alarm, Module Disconnect. Siren mounted in engraved panel below switches.
2	STD	Antenna, Radio Coax Cables: Terminated behind driver's seat w/Power & Ground for each
11	STD	Dome Lights: Whelen Halogen: 2-banks of four (4) lights switched separately with Hi/Lo functions; 1-bank of three (3) lights centered over cot, switched separately with Hi/Lo functions.
1	STD	Action Area Light: 16", 12 VDC LED Strip light, 18 diodes and On/Off switch on rear control panel
1	STD	USB Port: Vanner VSS-USB dual port 2Amp mounted on A/A wall
1	STD	Shoreline: 125 VAC, 20-Amp, 60 Hz, straight blade inlet w/hinged, weatherproof cover, located above Compartment #2 SS
2	STD	Switch, Momentary Disable: For Scene/Load Lights. (1) Located on Curbside Wall in 4-position plastic bezel: MX01507. (1) Located on Rear Curbside wall in standardized position, no bezel required, vertical S.S. trim is punched for switch.
1	STD	Timer: 5-minute check-out, wired to CS High mode dome lights
1	STD	Inverter: Pre-Wire w/switch on rear panel. Pre-wire located in ceiling of Compartment #2
1	STD	Battery Conditioner: Power Source, 45-Amp- Ceiling of Compartment #2
2	STD	12 VDC Outlets: (1) in Action Area, (1) in ALS Cabinet, (1) in 2nd Action Area
2	STD	125 VAC Outlets: Duplex, located (1) in Action Area, (1) in ALS, (1) in 2nd Action Area
1	STD	Breaker Box: 125 VAC w/20-Amp Breaker located in upper LH corner of exterior compartment #2. GFI receptacle located on the Action Area wall.
1	STD	Spotlight: 400,000 CP handheld, hard wired, w/momentary On/Off switch, located in cab
1	STD	Rear Switch Panel: Engraved black plastic panel with (14) LED lighted switch positions for Dome Lights (3), Vacuum (1), Vent (1), A.A. Light (1), Inverter (1), AC/Heat (1), Fan Speed (1), Spare switches, Thermostat and digital clock w/Mode Buttons. MX01516.

1	STD	Electrical Cabinet: Located over pass-thru w/latching, recessed, vented door
	05-	Warning Lights & Siren
1	STD	Lights; Warning, Whelen LED EMERGENCY Lighting Package- Ford, Chevy Type I and Type III- MSV-II Models ONLY. NOTE: Does not include LED Scene or Load Lights.
		DELETE All standard halogen WARNING Lights.
		All LED lights shall have CLEAR Lenses. All emergency and scene lighting shall have chrome flanges in standard locations.
		Front of Body: Add (7) Whelen 900 Series Suprer-LEDs- Specify pattern by LED Color (Red or White): _____ Outer (2) lights and (1) Center light flash on K-Spec flasher. Inner (4) flash independently on Light Bar switch on front console.
		Sides of Body: (4) Whelen 900 Series Red Super-LEDs: (2) each side in upper corners
		Rear of Body: (4) Whelen 900 Series Red Super-LEDs: (2) in upper outboard corners, (2) Mid-Body wired as Warning/Brake at the window level; (1) Whelen 900 Series Amber Super-LED in the center position over the rear doors.
		Brake, Turn & Back-Up Lights: Whelen 600 Series LEDs, (60BTT, 60A00TAR, 60C00VCR)
		Lights, Warning, Intersection Lights: (2) Whelen LINZ6 Series Red Super-LEDs on Front Fenders; (2) Whelen 700 Series Red Super-LEDs above rear Wheel Wells- wired to Pri/Sec Modes
2	STD	Lights, Warning, Grille: Whelen LINZ6 Red LED, on center grille bar, w/Clear lenses and flanges.
4	STD	Lights, Scene: Whelen 900 Series Halogen w/8-32 degree optics, (2) each side
2	STD	Lights, Load: 9Whelen 900 Series Halogen w/8-32 degree optics, (2) rear
1	STD	Flasher: Dual mode flasher for Warning Light system, Vanner 9860GCPE
2	STD	Siren Speakers: dual 100 Watt drivers mounted through the front bumper
1	STD	Siren- Whelen 295 SLSA1, 200 Watt
	06-	Oxygen, Vacuum & Miscellaneous Items
3	STD	Oxygen Outlets: Quick-connect style, 2-in Action Area, 1-over Squad Bench
1	STD	Electric Oxygen with manual bypass and switch on A/A panel
1	STD	Suction Aspirator System: SSCOR disposable container mounted in recess below Action Area, w/SSCOR gauge and quick-connect in recessed area; GAST vacuum pump mounted on ceiling of Compartment #2.
1	STD	Oxygen Cylinder Retention: Universal for "M" or "H" cylinder, steel w/3-spring buckle straps and top collar, powder-coated Safety Yellow color- in Compartment #1.
1	STD	O2 Regulator: Amvex, 50psi, pre-set
	07-	AC/Heat
1	STD	HVAC System: High capacity Free Blow combination Heat-AC system, multi-speed fan and thermostatic control in Action Area. HVAC unit mounted above ALS cabinet.

08-		Cabinets, Hardware & Miscellaneous Items
1	STD	Main Streetside Wall Cabinets: Specify desired configuration-
0	STD	Full Wall of Cabinets
0	STD	Main Wall Cabinet Configuration:- CPR Seat w/EVS V-4 seat belt system and 2nd Action Area for monitor mounting; includes (1) 125VAC and (1) 12VDC outlet in 2nd Action Area
		Main Wall Cabinets: Shall have (1) adjustable shelf in each and sliding Lexan doors with full height extruded handles. I/O access to compartment #3 shall be (2) 1/2" Acrylic, hinged doors with 2" round stainless steel Southco latches. See Prints for Configuration.
1	STD	Action Area Overhead Cabinet: <u>Single cabinet full-height/full-depth of Action Area</u> with sliding Lexan doors and full height extruded handles.
1	STD	Action Area and Switch Panel: Laminated, sealed countertop and vertical panel with Suction system collection cannister, Vacuum gauge, (2) Oxygen outlets, (1) 12VDC Outlet, and (1) 125VAC Outlet. <u>Switch panel includes (14) switch positions, Thermostat and digital clock w/Mode Buttons. MX01516</u>
1	STD	Corian Countertop - 1st / 2nd Action Area, Color: _____ w/ _____ Top and perimeter accent lips. To extend over the edge of cabinet main
2	STD	Bulkhead Wall Cabinets: Electrical Cabinet above walk-thru w/hinged, latching, vented door.
2	STD	Pass-Thru Cabinets: Upper cabinet- open storage w/hinged, latching door; Lower cabinet- open storage w/hinged, latching, vented door and location for inverter and vacuum pump on floor
1	STD	ALS Cabinet: Lower Section- Locking storage for box or bags w/LonPlate flooring; Middle Section- 6-inch deep drawer w/locking latch and gas strut closure w/Dri-Dek mat; Upper Section- w/ dual 1/2" Acrylic doors w/round SouthCo latches and (1) adjustable shelf w/ LonPlate flooring.
1	STD	Glove Box Holders: (3) w/hinged, powder-coated steel door, in pad above Curbside Entry Door
1	STD	Squad Bench:
	1	Full length hinged lid w/TriMark latch for access to interior storage
	2	Full length upholstered seat cushion except over Sharps/Waste Area; formed upholstered back rest cushions and head pad for each seated position.
	3	(2) EVS V-4 Belted seating positions w/(3) short bottom straps for 2nd Patient restraint
	4	Backer plate included in squad bench assembly at head end
1	STD	Cabinet, Squad Bench Overhead: w/ (2) flip-up 1/2" Acrylic doors with round SouthCo latches.
1	STD	Sharps/Waste: Drop-in style w/Red polycarbonate hinged lid with standard containers, located at head of squad bench.
1	STD	Technician's Seat: EVS Rear facing automotive style chair with Type II lap/shoulder belt mounted on swivel base.
1	STD	Seat Base: EVS SB-2 Swivel Base for EVS Technician's Seat
1	STD	Cabinet, Rear Overhead: Cabinet over rear door opening w/ (1) flip-up 1/2" Acrylic door w/round SouthCo latch
1	STD	Assist Rail: 1.25" Stainless steel w/radiused ends, overhead off-set toward Streetside.
3	STD	Grab handles: 12" x 1.25" dia. stainless steel mounted on each rear entry and curbside entry door
1	STD	Reflective Striping- Alternate Red/white chevron pattern on smooth aluminum kick panel- mounted on each rear entry and curbside entry door
9	STD	Reflective Striping, Door Open Protection: .50" Red reflective striping around interior door pan of all body doors
09-		Cots & Miscellaneous Items

0	OPT	Cot Mount: NOTE - Must supply cot mount requirements with order.
	10-	Paint & lettering
1	STD	Paint: Body all OEM White
0	1000100	Roof Star ONLY, INSTALLED
		SHIP LOOSE
2	STD	5 lb. Fire Extinguisher- Ship Loose
TOTAL ORDER		

I have reviewed this Order and find it to be acceptable and ready to build.

_____ **Date:** _____
 Dealer Signature

I have reviewed this Order and find it to be acceptable and ready to build with the addition of the attached, approved changes.

_____ **Date:** _____
 Dealer Signature

Due to on-going product improvements and the changing requirements of the ambulance industry, MEDIX Specialty Vehicles, Inc. reserves the right to change product specifications and related products without prior notice and without any obligation to change prior products or parts. ALL PATENTS RIGHTS RESERVED.